



# Finite Element Modeling of Army Airbeam Structures

May 4, 2005

JOCOTAS – Port Hueneme, CA

U.S. Army RDECOM - Natick Soldier Center Collective  
Protection Directorate, Fabric Structures Team  
Karen Santee – Project Engineer

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>04 MAY 2005</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-2005 to 00-00-2005</b>	
4. TITLE AND SUBTITLE <b>Finite Element Modeling of Army Airbeam Structures</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>U.S. Army Research, Development and Engineering Command,Natick,MA,02154</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT  <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES  <b>19</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			



# Agenda

- Brief Overview of Airbeams
- Engineering Process
- Modeling Approaches
- Fabric Airbeam Models
- Modeling Technical Barrier
- Cavity Filled Membrane Models
- Airbeam and Fabric Membrane Models
- Application of Modeling
- Center of Excellence
- Current Small Business Innovative Research Projects



# Brief Overview of Airbeams




- Load Bearing Pressurized Fabric Structures
- Pressurization pre-tensions the fibers, creating a structure that is rigid under design loads, but deflects without damage when overloaded
- Outstanding strength-to-weight ratio






# Engineering Process






# Modeling Approaches


Airbeam  
Fabric



Cavity Filled  
Membrane





Airbeam & Fabric  
Membrane






# Fabric Airbeam Models



Finite Element Results  
for Shear



Experimental Results  
for Shear





# Modeling Technical Barrier

## Barrier:

Test method to evaluate structural properties of fabrics subjected to combined multi-axial tension and shear loads for design purposes



## Problem:

Fabric elastic modulus & shear stiffness are dependent on:

- ✓ Fiber Directions
- ✓ Fabric Construction
- ✓ Tow Density Ratios (TDR)
- ✓ Coatings
- ✓ Inflation Pressure
- ✓ Structural Loads

## Solution:


A new test apparatus that can determine the pressure dependent elastic modulus and pressure dependent shear modulus.










# Cavity Filled Membrane Models



- Model results based on changes in cavity volume and inflation pressure
- Has begun to be explored and is in process of validation




# Airbeam and Fabric Membrane Models






# Application of Modeling

## Deployable Airbeam Fender System for the Joint High Speed Connector



Deflated





Inflated



# Verification of Model




Side View ~ 50% Compression






# Model Variations


## Scaled Prototype Model




## Partial Air and Water Model



## Side View of Pinch Point



## Partial Compression





# Center of Excellence Inflationary Composite Structures


**Increase durability, reliability  
and affordability**

**Establish predictive  
design tools and models**

**Market and Document  
Technology**

**Partner with DoD and  
government agencies,  
industry, and academia**

**Broaden inflationary structure  
applications and commercialize  
the technology**



**Vision**

**Deliver new inflationary technology into  
the hands of warfighters and commercial users.**

**(Established in 2001 at the Natick Soldier Center in Natick, MA)**





# Small Business Innovative Research Project

- Flexible Display
  - Physical Optics Corporation
- Solid State Lighting
  - Space Hardware Optimization Technology
  - Physical Optics Corporation
- Photovoltaic Power Shade
  - Iowa Thin Film Technologies
- Insulation
  - Aspen Aerogels
  - L'Garde, Inc.








# Flexible Display

**POC** *Physical Optics Corporation*



## Capabilities:

- Ultra thin ( $<1$  mm), flexible (6-10 cm bending radius), high-resolution (100 mm pixel size, total up to  $640 \times 480$  pixels)
- Lightweight ( $<0.5$  g per  $1 \text{ cm}^2$  of display area,  $<100$  g for electronics)
- Full-color, real-time (30-60 Hz refresh), high-optical-contrast ( $>100:1$ ) display
- Scalability in the display area (from  $1 \text{ cm}^2$  to  $1 \text{ m}^2$  active area)
- Visual images, such as maps and drawings, will be displayed on shelter fabric



# Solid State Lighting


## Capabilities

- Evenly illuminates floor level (one fixture for 1 m<sup>2</sup>) 3 m<sup>2</sup> in near future
- Permanently attached to shelter (deployed together)
- Operates from outside power or from battery 100,000 hr. lifetime
- Runs 6 hr. on 5 AA batteries with power shutoff
- 10 times longer life than fluorescent light
- Compact, lightweight (100 g fixture)
- All light is directed to the floor (no dispersed light)
- Solar spectrum
- Low cost in mass production (\$5/fixture)



SOSIL Luminaire

**POC** *Physical Optics Corporation*





# Photovoltaic Power Shade

## ***"Power Shade"***

### Application:

- Solar shade w/ integral PV power
- Provides 1 Kw of PV power, reduces solar load 80% – 90%
- Design to fit over: MGPTS small, 16' TEMPER
- Modular expandability



Dimensions: 22' x 20' x 10'9" - 14'6"

Power: ~1 Kw

Operating Voltage: 12V

BOS required

PV combiner boxes  
Master disconnect switch  
Charge controllers  
12V Deep cycle batteries  
Inverter for 120 VAC use





# Insulation



- Aspen Aerogels

- 85% Packing Cube Reduction
- R-value  $> 6$  °F·ft<sup>2</sup>·hr/Btu
- Flame Resistance
- 99% Open Porosity
- Noise and IR Suppression
- Phase II partner with Johnson Outdoors



MIL-C-44154B

Aspen Insulation

- L'Garde

- Phase III
- R-value  $> 6$  °F·ft<sup>2</sup>·hr/Btu
- Weight  $< 20$  oz/yd<sup>2</sup>
- Demonstrated 65% reduction in heating/cooling power requirements
- Automated fabrication
- Adjustable to fit multiple shelter geometries





# Thank You